

ML4701 transmitter

Pro ML4700 LUX/UV Series

Part of the **Hanwell Pro** ML4000LUX/UV series, the ML4701 transmitter accurately measures light (LUX) using an onboard sensor and 434.075MHz frequency as standard.

Features

- ✓ Accurate light (LUX) measurement
- ✓ Superior performance hardware & high accuracy sensors
- ✓ Easily accessible battery & USB socket
- ✓ Low power radio for long distance transmission (3km over open ground)
- ✓ Complies with RoHS, EU & WEEE directives
- ✓ Carries CE Marking

Typical Applications

- Museum artefact preservation
- Medical supply storage

Always ask for a long-range signal strength test.



We can prove ours to be unrivalled.



LUX



Radio transmitter

Instrumentation specification

| | |
|-------------------------------|---|
| Dimension (Excl. ancillaries) | 110 x 80 x 35mm |
| Weight | 200 grams |
| Power supply | 1 x 3.6V AA Lithium battery |
| Case material | ABS & PC |
| Memory capacity | 100,000 readings per channel (unit will wrap when full) |
| Clock accuracy (logging) | 20ppm @ 25°C |
| IP Rating | IP30 |
| Instrument operating range | 0°C to +50°C in a non-condensing RH environment |
| Storage temperature | -40°C to +60°C |

Accessories

| | |
|-------|-------------------------|
| 88706 | 3.6V AA Lithium battery |
| Y119 | Wall mount bracket |

Radio transmitter functions

| | |
|------------------------|---|
| Frequency options | A range of frequencies are available between 433-458MHz. Country specific regulations apply. |
| Radio power | 10mW |
| Radio range | 3km over open ground |
| Battery life | Up to 2 years (dependent on conditions of use and instrument settings) |
| Software required | W900 – Standard EMS Software Package W906 – Validated EMS Software Package *See EMS datasheet for further options |
| Software compatibility | EMS - All Versions Synergy - All Versions RadioLog 8 |
| Hardware required | CR2 / CR3 – Controller SR2 – Smart Receiver REP – Repeater |

Manufactured by Hanwell | Ellab   RoHS

Version 4 - EC200121

Disclaimer: The information contained herein is believed to be reliable. Hanwell Solutions Ltd. is not responsible for any incorrect or incomplete information on this datasheet and the information or product may be changed without notice. Customers should obtain and verify the latest relevant information before placing orders for Hanwell products.

hanwell.com

Tel: +44 (0)1462 688070 | Email: sales@hanwell.com

Sensor (supplied with unit)

| LUX sensor | Photometric diode detector |
|--------------------|------------------------------------|
| Visible wavelength | 400 to 700nm |
| Visible range | 10 to 5000 LUX |
| Colour response | Human eye (Match to CIE Curve =5%) |
| Linearity | 1% |
| Angular response | Cosine |
| Long term drift | <1%FS per year |

Manufactured by Hanwell | Ellab   RoHS

Version 4 - EC200121

Disclaimer: The information contained herein is believed to be reliable. Hanwell Solutions Ltd. is not responsible for any incorrect or incomplete information on this datasheet and the information or product maybe changed without notice. Customers should obtain and verify the latest relevant information before placing orders for Hanwell products.



TR instruments
 Tel.: +420 541 633 670
 Fax: +420 541 212 413
 Křižíkova 70, 612 00 Brno
tri@trinstruments.cz

hanwell.com

Tel: +44 (0)1462 688070 | Email: sales@hanwell.com